

MOTOR SPECIFICATION		CONNECTION	
		UNIPOLAR	SERIES
Voltage	V DC	2.66	
Current per Winding	A	0.95	0.67
Resistance per Phase (25°C) ±15%	Ω	2.8	5.6
Inductance per Phase (1 kHz) ±20%	mH	0.85	3.4
Holding Torque	Nm	0.043	0.061
Step Angle ±5%	°	1.8	
Rotor Inertia	kg m²	0.9 x10^{-6}	

7

JST XHP-6



TYPE OF CONNECTION				
Unipolar	Series	Pin No.	Wire Col.	Winding
A	A	1	BK	A
COM		5	YE	COM
A\	A\	3	GN	A\
B	B	2	RD	B
COM		6	WH	COM
B\	B\	4	BU	B\



Max. Axial Force	Fa	N	7
Max. Radial Force	Fr (a1 = 5 mm)	N	58
Max. Radial Force	Fr (a2 = 20 mm)	N	20
Axial Play	Fa = 10 N	mm	0.075
Radial Play	Fr = 5.0 N	mm	0.025

GENERAL MOTOR SPECIFICATION		
Ambient Temperature	°C	-10 ...50
Max. Temperature Rise (at standstill - 2 phases energized)	°C	80
Max. Ambient Humidity (non condensing)	%	85
Insulation Class		B
Insulation Resistance	MΩ	100
Dielectric Strength (for 1 min - coil to case)	V AC	500

ISO 8015	ISO 1302	ISO 2768 cK	ISO 13715	Replacement for drawing from 06.06.06	Weight: ±10% 0.11 kg

					Date	Name
				Drawn	29.11.2023	Schneid_A
				Reviewed	06.12.2023	Reith_S
				Released	06.12.2023	Reith_S
07	modified prod. process	Schneid_A	07.12.2023			
REV	Rev. Text	Name	Date			

Nanotec® PLUG & DRIVE

ST2818S1006-B

20002190

A4 Page 1

State: Released | Rev: 07 | CONFIDENTIAL